

Product Description

C525 is a laminated aluminium foil/PE mesh with a synthetic rubber resin adhesive system on a siliconised paper release liner



Product Features

- A Polyethylene Non-Woven Mesh with a thin aluminium facing
- Hand-tearable
- Thermal range to 80°C permanent
- Aggressive synthetic rubber adhesive with high bond strength
- Available in 50 Metre rolls in widths from 12mm to 1,000mm (for custom lengths contact Customer Service for MOQs)

Benefits

- ✓ Reinforced for greater structural and tensile strength than plain foils
- ✓ Suitable as a vapour seal
- ✓ Good adhesion to self
- ✓ Flame retardant—Tested to AS1530.3 –1999
- ✓ Easily hand torn
- ✓ Good adhesion to self and other aluminium faced products e.g. ductwork
- ✓ Good UV resistance and high reflectivity

Key Markets

- HVAC Duct sealing and as a vapour seal in sheets and boards in the building industry
- Joining roofing insulation
- Sealing lagging in pipework and refrigeration and cold store industry
- Radiant shielding and heat reflection
- Joining foil-faced glass fibre or rockwool
- Sealing double glazing units
- Hand-tearable repair tape that can be painted over



DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.