

Product Description

E3800 is a Grey resilient skived polyurethane Anti-slip surface on a cloth backing with a siliconized paper release liner



Product Features

- A tough, resilient, UV stable polyurethane finish on a rayon cloth backing
- The soft but gripping polyurethane gives a P4 Slip Rating
- Solvent acrylic adhesive system and paper release liner
- Cut to widths down to 6mm in 20 Metre length and also available in a retail 5 Metre Pack 25 & 50mm

Benefits

- ✓ Ideally suited for washrooms and changing rooms (people with bare feet)
- ✓ Excellent grip for both soled footwear and bare feet or hands. Does not abrade and damage clothing as with grit tapes
- ✓ Grey surface is good at concealing dirt and so easier to keep clean
- ✓ Can be used on rounded rails and handles to enhance grip
- ✓ Due to cloth backing, lends itself to die cut shapes and pieces with a radius corner e.g. on shower and bath bases and on steps and staging

Key Markets

- Occupational Health & Safety from industry, building and construction, commercial
- Aged care and health care providers for both steps, ramps, rails and handles
- Marine sector both commercial and recreational
- Public sector, government buildings, airports, ports and military
- Safety equipment fabricators—ladders, gantries, staging, stair nosing
- Sports facilities, building and hardware
- Schools and Tertiary Training establishments
- Resources sector both onshore and offshore
- Signage industry for floor graphics
- Portable buildings, site huts, washrooms and toilets
- Transport—tailgates, ladders, foot holds, running boards, step areas
- Mechanical equipment including earth moving, cranes and agricultural equipment
- RV market—caravans, campers and trailers
- Film & TV studios, equipment and vehicles
- DIY applications—retail packs



DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.