

### Product Description

**U350** is a Double Sided Polyester Tape with a high performance acrylic adhesive system on either side of a rust coloured filmic release liner



### Product Features

- A strong, clear PET filmic backing
- A Low Surface Energy high tack modified acrylic adhesive with high coat weight on both sides
- A high quality rust coloured filmic release liner

### Benefits

- ✓ Designed for the permanent mounting of badges, nameplates, trim, data strip etc
- ✓ The PET carrier gives good clarity and allows re-positioning during application
- ✓ This product has an upgraded Low Surface Energy modified acrylic adhesive system which gives a high initial tack allowing bonding to a wide range of substrates
- ✓ Incredibly versatile performance across a wide range of substrates and surface conditions including slightly rough or textured surfaces
- ✓ It has a very good resistance against UV radiation, extreme temperatures, chemicals, solvents and humidity
- ✓ Suitable for lamination to material in wide width, up to 1,040mm and as cut rolls from 4mm to 1,040mm in either 50 or 200 Metre length

### Key Markets

- Sign and Display for the permanent mounting of small signs and name plates
- Attachment and mounting of trims, decorative moulds, covers, cable trunks etc in both extruded plastic, rubber, ABS, wood and metal finishes
- For merchandising and mounting of short-term promotional signage
- Joining and splicing of paper, textiles, plastic and metal films, particularly where high shear strengths required
- Mounting of inserts in metal and plastic profiles e.g. stair nosings, decorative trim
- Curtain and blind trade for the holding of fabrics to splines, rollers, pelmets etc
- Mounting of rubber and EPDM profiles for sealing applications
- Mounting of circuit boards, battery packs and touch screens in electronic devices

### Applications



Decorative trim



Nameplates



Extruded plastic profiles

#### DISCLAIMER:

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**