

Product Description

U973 is a translucent premium grade double sided rayon backed cloth with a solventless acrylic UV cured adhesive System with a Havana coloured siliconized paper release liner



Product Features

- High coat weight of adhesive at 0.30mm (thicker gauge available by request)
- Special solventless acrylic adhesive – resistance to plasticiser migration (makes this a very rare beast)
- Great cohesive strength and so, good clean remove characteristics but also fantastic quick stick
- High tensile but easy tear rayon cloth backing
- Very high thermal range for a Double Sided Cloth, to 80°C

Benefits

- ✓ Suitable for use of rough or textured surfaces due to its conformability
- ✓ Good UV stability and ageing characteristics, so can be used for certain outdoor applications
- ✓ Due to high cohesive strength of its adhesive system can be used for both permanent and temporary applications (always test on surfaces for clean removal)
- ✓ Can be used on both concrete, stone and wooden surfaces
- ✓ Removes without breaking or leaving a residue (Note this applies to stable surfaces but testing always recommended prior to use as any surface treatment can effect performance)
- ✓ Its acrylic adhesive system makes it particularly suitable for use on vinyl floor finishes (also see our KK915 Acrylic Resin Cloth Double Sided Tape)

Key Markets

- **Exhibition & Display** For the holding of all types of floor coverings, particularly where clean removal is an important criteria for use
- **Film & TV** A highly versatile double sided tape for the holding of props & scenery and temporary floor coverings
- **Building & Construction** For the holding of PE sheeting e.g. asbestos removal, render protection. For the holding of all types of floor coverings both temporary and permanent e.g. Anti-fatigue matting, retail carpeting and mats. Holding sandpaper to grind stones/rotary discs. Mounting of synthetic profiles and rubber mouldings for shop/office fit out
- **Permanent Carpet & Vinyl Laying** Particularly suited for the laying of PVC flooring and foam-backed carpets as offers good resistance to plasticisers
- **Printing** Bonding rubber blocks in flexographic printing

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.