

Product Description

S1325 & S1328 are a fibre-filled modified solvent acrylic transfer tape Supplied on an Orafol™ branded moisture stable kraft paper release liner



Product Features

- A 60 & 120µm film of extreme high tack low surface energy fibre- filled transfer adhesive
- Supplied on an Orafol™ Branded Printed moisture stable siliconized PE coated kraft paper release liner and Orafol™ branded printed cardboard core
- Available in widths from 6mm to 1,220mm in 50m length

Benefits

- ✓ Excellent 'quick-stick' and shear — designed for lamination to fabrics, foams, felts and other textured surfaces
- ✓ The adhesive has an excellent blend of adhesive and cohesive strength making it highly versatile for a wide range of applications, stable to 150°C permanent and 190°C short term
- ✓ The fibre-fill to this transfer adhesive makes it easy to work with and remove from release liner due to the tear characteristics
- ✓ High quality, moisture stable release liner for ease of application and removal
- ✓ Tape Certified according to UL 969 (Standard for marking & labelling systems)

Key Markets

- For lamination on a wide range of fabrics, films, foams, rubbers, felts and other materials to make them pressure sensitive
- Labels & badge mounting applications
- In the graphics and sign industry on a wide range of media for mounting applications
- Paper and cardboard industry for splicing and holding applications
- For creation of gaskets and seals in industrial applications
- For the mounting of thermal and acoustic insulation
- Creating of swatch cards, sample books for a wide range of fabrics, vinyl files and other finishes
- Fabrication and joining of polypropylene Flute Board for packaging and protection
- Bonding to media for Laser cut, laser engraved or laser etched surfaces
- As a pre-stitch for joining materials prior to sewing
- Picture framing, sporting memorabilia, craft work and scrapbooking

Applications



DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.